

PRESSURE RELIEF VALVES AND COMMERCIAL SAFETY RELIEF VALVES

6



**P&T – PRESSURE AND TEMPERATURE RELIEF VALVES**

Fully automatic temperature and pressure relief valve. Protection for domestic installations of unvented water heaters, to prevent the temperature of water exceeding 100°C.  
 Pressed DZR brass body BSP threads.  
 Ethylene-propylene diaphragm.  
 Temperature setting 93/94°C.



**WRAS Approved**

Pressure	Part number	Size body	Box Qty
7 BAR	68000	M/F 1/2"	10
7 BAR	68003	M/F 1/2" x15mm	10
10 BAR	68002	M/F 1/2"	10
1.5 BAR	68812	M/F 3/4"	10
4 BAR	68815	M/F 3/4"	10
4.5 BAR	68816	M/F 3/4"	10
6 BAR	68520	M/F 3/4"	10
7 BAR	68620	M/F 3/4"	10
8 BAR	68720	M/F 3/4"	10
9 BAR	68830	M/F 3/4"	10
10 BAR	68820	M/F 3/4"	10

C



**SERIES 174A SAFETY RELIEF VALVE**

Bronze body safety relief valve for all types of hot water boiler equipment with manual lever.  
 Pressure range 30 to 150 psi (2 to 10 bar).  
 Operating temperature range Min. 1°C Max. 140°C.  
 Bronze body screwed BSP Female.  
 Stainless steel spring.  
 Teflon seat (avoids sticking).  
 EPDM membrane.  
 Available to order – other set pressures.

Pressure	Part number	Size body	Box Qty
3 BAR	EDP279030	3/4"	1
7 BAR	EDP279070	3/4"	1
3 BAR	EDP279150	1"	1
7 BAR	EDP279190	1"	1
3 BAR	EDP279220	1-1/4"	1
7 BAR	EDP279250	1-1/4"	1
3 BAR	EDP276487	1-1/2"	1
7 BAR	EDP276490	1-1/2"	1
3 BAR	EDP279320	2"	1
7 BAR	EDP279370	2"	1



**N36 VACUUM RELIEF VALVE**

Water services vacuum relief valve. Automatically vents a closed system if vacuum occurs. Relieves vacuum conditions which would siphon the water from the system and burn out a water heater or collapse a tank.  
 Max. operating pressure: 13.8 bar. Max. operating temperature: 121°C.  
 Venting capacity 425 litres/min (air).

Type	Part number	Size body	Box Qty
N36	EDP138457	1/2"	1
N36	EDP0138458	3/4"	1